

ROOF TILE GUARD

Tile guard is one of the premium range product of NOELCOAT which has been formulated by a various research carried by the R&D department of NOELCOAT. Extreme levels of heat, rain and cold are easily ensured by the Tile finish. An optimal shield is being provided in the form of Tileguard for the roof. The particular elastomeric effect of it expands and shrinks along with the roof tile and so the paint can persist for long. It contains special additives which provide extreme protection from alkali and ultra Violet Rays.

HOW TO APPLY



New masonry surface must be allowed to cure completely. It is recommended to allow 28 days as the curing time for new masonry surface



To enhance the performance of the paint film clean the surface from any loose paint, dust, grease. Growth of fungus, algae or moss should be removed by wire brushing and water



To enhance the performance of the paint, ensure proper washing and cleaning of all algal and fungal growth, if any at regular interval of six months



PAINT APPLICATION PROCESS

Application	Thinner	Dilution %	Recoating period
Step 1: First coat Noelcoat Roof tile Guard by Brush/spray	Water	300ML water	4HRS
Step 2: Second coat Noelcoat Roof Tile guard by Brush/spray	Water	300ML water	4HRS

FEATURES

Additives	Usage	Advantages
Water Repellent	The tough paint film does not allow water penetration	Tile/Roof remains rich and beautiful for long time.
Elastomeric	Flexibility of Paint Film	Do not break Paint Film
Dry Film	Anti Algae/Anti Fungi	Tile/Roof remain Spotless for Long

DURABILITY

Best In Class High Medium Low

AREA OF APPLICATION	POT LIFE OF THINNED PAINT
Exterior <input checked="" type="checkbox"/>	Used Within 24 HRS
Interior <input type="checkbox"/>	

APPLICATION ENVIRONMENT	SAFETY FEATURES
Temperature: 10°C-28°C Digree Humidity: Below 80%	Non-flammable No added Lead, Mercury or Chromium compounds

Discription	Pure/Elastrometric Polymer
Viscosity	120 second at 28°C, when thinned with 1:1 water
Ph	8.5
Weight/Ltr	1.1±2
Thinning Media	Potable Water
Thinning Ratio	300ml/Ltr
Coverage	80 Tile on Paved
Finish	High Gloss
Area of Application	Earthen Tile, Brick, Concrete, Asbestos
Method Of Application	By Brush/Roller/Spray
Surface Dry (28-30°C)	4 to 6Hrs
Hard Dry	24Hrs
Second Coat interval	4 Hrs after First coat
Storage	Keep away from direct sunlight and excess heat
Shelf Life	2 years
Usage	Both Exterior and interior Walls